



# GXP<sup>®</sup> sensor model solutions

At the heart of photogrammetry, sensor models incorporate complex equations relating the positions of points within a region, such as a specific building in North America, to their positions on images acquired by sensors. In addition, these models enable the estimation of parameters specifying the position, attitude, and movement through time of the respective sensor.

Sensor models expedite rigorous error propagation, so that measurements on images result not only in positions, angles, and distances, but also in estimates of the accuracy of these derived quantities. These models are essential not only to image registration, but to all subsequent stages of the photogrammetric workflow, including terrain generation, feature extraction, and visualization.

Adhering to prevailing international standards, GXP<sup>®</sup> software is renowned for its wealth of sensor models, supporting numerous electro-optical, infrared, multispectral, hyperspectral and synthetic aperture radar (SAR) and LiDAR sensors. Many GXP sensor models are rigorous (i.e., they mathematically model the physical characteristics of the sensor), providing a degree of accuracy far above standard models which generally fit the physical system but don't replicate its inner structure.

Multiple sensor models often operate simultaneously in GXP software, facilitating a powerful fusion of data to maximize the accuracy of information while enabling advanced exploitation of a rapidly growing population of image sources worldwide.

Photogrammetric sensor models developed by Geospatial eXploitation Products™ (GXP) provide a geometric representation of how light is reflected off of the object of interest, delivered through the air to a camera (sensor), and then converted into pixels for visualization.

This approach applies equally to active sensors, such as LiDAR and SAR, which transmit energy to the object to be measured and then receive the reflected signal.

GXP sensor models support accurate determination of key measurements and advanced geospatial workflows.

- » Ground coordinates
- » Distance measurements
- » Height measurements
- » Feature extraction
- » Triangulation
- » Terrain generation
- » Orthorectification
- » 3-D modeling
- » Error propagation

**GXP**<sup>®</sup> Geospatial solutions  
to ensure **a safer world.**

GXP supports the full life-cycle of sensor model development including the following:

### Design & Development

Design, development, and testing of the sensor model, including development of synthetic image data when actual data is unavailable.

### Verification

Rigorous testing using ground truth to determine accuracy. All test results are analyzed and addressed by an expert team of photogrammetrists and identified issues are addressed appropriately.

### Validation Support

Comprehensive support during the entire validation process including document preparation, technical support throughout testing, and development of recommendations.

## Sensor models utilized in SOCET GXP®

- › ADS40/80/100
- › ALOS AVNIR-2/PRISM/PALSAR/PALSAR-2
- › Arc Standard Raster Product (ASRP 1.2)
- › ASTER
- › Cartosat
- › Chandrayaan-1 TMC
- › Common Coordinate System (CCS) mosaic
- › Community Sensor Model (CSM) support for user-developed sensor models
- › Compressed ARC Digitized Raster Graphic (CADRG)
- › COSMO-SkyMed (complex and detected)
- › Digital Point Positioning Database (DPPDB)
- › Direct Linear Transformation
- › Earth-i DMC3
- › EROS-B
- › FORMOSAT-2/5
- › Four-Corner
- › Frame Advanced
- › Generic Point Cloud Model (GPM)
- › Generic 2D/3D polynomials
- › GeoEye-1
- › IKONOS
- › KOMPSAT-2/3/5
- › Landsat
- › Mensuration Services Package (MSP)
- › NCDRD (National Imagery Transmission Format v2.1 Commercial Dataset Requirements Document)
- › Ortho
- › PeruSat-1
- › PlanetScope
- › Pleiades
- › Predator
- › Quickbird
- › RADARSAT-1 Orbit Aligned
- › RADARSAT-2 North Aligned and Orbit Aligned (complex and detected)
- › Rational Polynomial Coefficients (RPC)
- › Replacement Sensor Model (RSM)
- › RISAT-1
- › SENSRA
- › SENSRB
- › Sensor Independent Complex Data (SICD)
- › Sensor Independent Derived Data (SIDD)
- › Sentinel-1A/2A/2B
- › SkySat
- › Smart Image
- › SPOT (1-3, 5+)
- › TanDEM-X (complex and detected)
- › TeLEOS-1
- › TerraSAR-X (complex and detected)
- › United States Geologic Survey Digital Ortho Quad and Quarter Quad (USGS DOQ)
- › USMSD
- › VisionMap A3
- › WorldView-1/2/3/4

*This list is not indicative of the full range of data that can be opened and exploited in SOCET GXP, but is intended to show the sensor models that can be initialized.*

#### Americas

Tel 800 316 9643  
gxp.sales@baesystems.com

#### Asia

Tel +603 2191 3000  
gxp.sales.asia@baesystems.com

#### Australia and New Zealand

Tel +61 2 6160 4000  
gxp.sales.apac@baesystems.com

#### Europe, Middle East, and Africa

Tel +44 1223 370 022  
gxp.sales.emea@baesystems.com